

HYFLEX FLOOR SEAL

Premium Total Floor Treatment



This unique floor treatment is a blend of four polymers that exhibit amazing properties. It has exceptionally long life and has excellent soil resistance. Designed for use on floors in areas of heavy traffic. It is a water based emulsion seal that is fast drying, has low odour, non-flammable and easy to apply. Hyflex produces a clear coating with a superb lustre without the hazards of solvent based floor seals.

- Easy clean—soil just falls away from the surface
- No need to protect with floor finish
- Easy to buff to rejuvenate gloss or lustre
- Reduces the overall cost of product and labour
- Apply up to 2 coats neat
- 25-40sqm per L coverage depending on floor surface



APPLICATION

For use on terrazzo, stone, concrete, porous composition, linoleum, vinyl, thermoplastic and wood floors.

Thoroughly clean floor with a single brush rotary machine fitted with black pad, using appropriate stripping solution to remove all remnants of old polish and soil. Allow the floor to dry thoroughly and inspect the floor to make certain that it is spotlessly clean. The floor must be clean from all contamination. The floor is now ready for the application of Hyflex. When required, Hyflex can be removed using Heavy Duty Polish & Seal Stripper.

With a flat mop applicator, apply a generous even coat of seal. Do not leave puddles and make certain the correct amount of seal is used. Take care not to overlap coats and apply every coat in the same direction. Allow the first coat to dry thoroughly (one hour is normally sufficient). Then apply one or two further coats evenly to the floor surface allowing each coat to dry thoroughly.

Touch dry: 1 hour | **Hard dry:** 2 hours | **Foot traffic and normal wear:** 8 hours | **Full chemical hardness:** 7 days

PACKAGING

Order Code : Y-CS76

Pack Size: 2 x 5L

STORAGE

Store in the sealed original container out of direct sunlight. Protect from freezing.

Keep out of the reach of children.